


SPECIFICATION CONTROL DRAWING



NOTES

1) D6021-XXX CROSSTUBE
LENGTH

WHERE XXX IS LENGTH IN INCHES
EG. 125" LONG TUBE: D6021-125

2) MATERIAL: 17-4PH SEAMLESS STAINLESS STEEL TUBE PER ASTM A564
 $\text{Ø}2.378$ O.D. x $\text{Ø}2.000$ I.D.

HEAT TREAT TO H1025:
MIN. ULTIMATE TENSILE STRENGTH = 155 ksi
MIN. YIELD TENSILE STRENGTH = 145 ksi

3) TOLERANCES ARE AS FOLLOWS:
ECCENTRICITY: 10% (+/-0.018" WALL)
LENGTH: XXX +0.188"/-0.000"
STRAIGHTNESS: 0.012" DEVIATION / 12" LENGTH

4) ALL DIMENSIONS ARE IN INCHES
5) TUBE MUST BE PICKLED OR ELECTROPOLISHED TO BE SMOOTH AND FREE FROM SCALE.
6) EXTREME CARE MUST BE TAKEN TO PROTECT THE OUTSIDE SURFACE OF THE TUBE. THE OUTSIDE SURFACE MUST BE SMOOTH AND FREE FROM SURFACE DEFECTS SUCH AS SCRATCHES, NICKS, OR DENTS. DEFECTS UP TO 0.005" MAY BE BLENDED OUT LONGITUDINALLY. CIRCUMFERENTIAL GRIND MARKS ARE UNACCEPTABLE.

PRELIMINARY ISSUE

9/14/6/3

PA5	NEW ISSUE	CP	14.06.03
REV.	DESCRIPTION	BY	DATE
DESIGN	q	DART AEROSPACE LTD HAWKESBURY, ONTARIO, CANADA	
DRAWN	q		
CHECKED		DRAWING NO.	REV. PA5
MFG. APPR.		D6021	SHEET 1 OF 1
APPROVED		TITLE	SCALE
DE APPR.		CROSSTUBE MATERIAL	NTS
DATE	14.06.03	COPYRIGHT © 2014 BY DART AEROSPACE LTD THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE LTD.	